

SC-02 V4 VIDEO INTERCOM

CUSTOMISE
your
INTERCOM
PLATE
see page X

- + Flush-mounted installation, surface-mounted box option
- + Hearing loop
- + Plate on swivel hinge
- + Invisible camera
- + Hands-free reader
- + 12 keys backlit coded keypad



INSTALLATION MANUAL



SC-02 VIDEO INTERCOM RANGE

| | | 1 INTERCOM | 1 INTERCOM + 1-DOOR CENTRAL UNIT // 200 NAMES | 1 INTERCOM + 2-DOORS CENTRAL UNIT // 1,000 NAMES |
|----------------|------------------------|------------|---|--|
| SC-02 | Stainless steel finish | 02-0182 | 02-0184 | 02-0185 |
| | Brass finish | 02-0183 | 02-0186 | 02-0187 |
| SC-02 Key safe | Stainless steel finish | 02-0189 | 02-0192 | 02-0193 |

ACCESSORIES

| | V4 Protective cap | Stainless steel finish | 12-0108 | W 155.50 x H 305.50 x D 35 mm |
|---------------------------------|----------------------------|------------------------|-------------------------------|-------------------------------|
| | V4 Key safe protective cap | Stainless steel finish | 12-0164 | W 155.50 x H 493.50 x D 71 mm |
| | V4 surface-mounted box | Stainless steel finish | 12-0160 | W 155.50 x H 305.50 x D 67 mm |
| | | Brass finish | 12-0178 | |
| V4 Key safe surface-mounted box | Stainless steel finish | 12-0159 | W 155.50 x H 495.50 x D 71 mm | |

INTERCOM

| DIMENSIONS (W x H x D) | V4 intercom V4 Intercom Key safe V4 back box | 150 x 300 x 2.5 mm 150 x 490 x 51 mm 126 x 274 x 45 mm |
|--------------------------|---|---|
| ENVIRONMENT | Operating temperature Index Protection | -20°C to +60°C IP54 / IK08 |
| ACCESS CONTROL EQUIPMENT | Coded keypad Hands-free reader Outdoor / Indoor Flush-mounted | ✓ ✓ ✓ ✓ |
| INSTALLATION | Surface-mounted Swivel hinge Accessibility Needs compliant Hearing loop Braille keypad Yellow highlighted buttons Time taken to connect | Surface-mounted box available as an add-on product ✓ ✓ ✓ ✓ 40 sec. |
| ADDITIONAL INFORMATION | Configurable welcome message (64 scrolling or static characters) Accelerated alphabetical searching Name or flat number displayed on time slots Display: 2 lines of 16 characters each Functional messages: (call in progress, etc.) Voice synthesis + display Anti-disturbance (I) Sound level adjustment without dismantling (depending on the associated central unit) Automatic call return if no answer | ✓ ✓ ✓ ✓ ✓ ✓ ✓ |

(1) System to prevent residents being disturbed by repeated calls

➔ MORE INFORMATION ON CENTRAL UNITS ? See pages XX and XX

SCROLLING INTERCOM

CENTRAL UNITS

| | 1 door - 03-0102 | 2 doors - 03-0101 |
|---|-------------------------|-------------------|
| CENTRAL UNIT CHARACTERISTICS | | |
| Maximum number of dwellings managed | 200 | 1,000 |
| Power supply recommended (not included) | 12 VDC 5A - 24 VDC 2.5A | |
| SYSTEM | | |
| Number of relays | 1 (+3) | 2 (+2) |

SERVICE PACKAGE CHOICE

Once you've selected your equipment, take out the package of your choice to ensure the intercom's functionality.

CLASSIC SERVICE PACKAGE

PREPAID 15 YEARS ALL INCLUSIVE PACKAGE

See pages XX and XX TO DISCOVER THE OFFERS

| | 4G-IP module | Deported |
|--|--------------|--|
| 4G-IP MODULE CHARACTERISTICS | | |
| Number of intercom(s) per 4G-IP module (video) | | 1 to 3 (depending on the type of central unit) |

SIMPLIFIED SCHEME* and WIRING

Ref: 03-0102

| | 1 door - 03-0102 | 2 doors - 03-0101 |
|----------------------------------|---------------------------|---------------------------|
| 4G-IP module Central unit | 4 wires (2 twisted pairs) | 6 wires (3 twisted pairs) |
| Central unit Intercom | 4 wires (2 twisted pairs) | 6 wires (3 twisted pairs) |
| Intercom 4G-IP module | 4 wires (2 twisted pairs) | 2 wires (1 twisted pair) |

*1-door central unit scheme. To view the 2-doors central unit scheme, you can scan the installation manual QR code