



SC-03 INTRACODE VIDEO INTERCOM

- + Surface mounting : **quick and damage-free**
- + **Ultra-resistant**
- + **Colour LCD display** with sensor for brightness adjustment
- + **Pinhole camera**
- + **Handsfree reader**
- + **12 keys backlit** coded keypad



INSTALLATION MANUAL



Intracode anthracite finish 01-0201

CUSTOMISE
your
INTERCOM
PLATE



CUSTOMISE
THE SCREEN
with
YOUR LOGO
see page XX



SC-03 VIDEO INTERCOM RANGE

SC-03	Anthracite finish	1 INTERCOM 01-0201	1 INTERCOM + 1-DOOR CENTRAL UNIT // 200 NAMES 01-0203	1 INTERCOM + 2-DOORS CENTRAL UNIT // 1,000 NAMES 01-0202
-------	-------------------	-----------------------	--	---



DESCRIPTION and TECHNICAL SPECIFICATIONS

INTERCOM

DIMENSIONS (W x H x D)	Intracode intercom	135 x 340 x 28 mm
	Intracode wall mounting	115.90 x 290.20 x 21 mm
ENVIRONMENT	Operating temperature	-20°C to +60°C
	Index Protection	IP54 / IK08
ACCESS CONTROL EQUIPMENT	Coded keypad	✓
	Hands-free reader	✓
INSTALLATION	Outdoor / Indoor	✓
	Surface-mounted	✓
	Accessibility Needs compliant	✓
	Hearing loop	✓
	Braille keypad	✓
	Time taken to connect	40 sec.
	Accelerated alphabetical searching	✓
	Name or flat number displayed on time slots	✓
	7 x 5.3 cm colour LCD screen	✓
	Functional messages: (call in progress, etc.) Voice synthesis + display	✓
ADDITIONAL INFORMATION	Anti-disturbance (I)	✓
	Sound level adjustment without dismantling (depending on the associated central unit)	✓
	Automatic call return if no answer	✓

(1) System to prevent residents being disturbed by repeated calls

➔ MORE INFORMATION ON CENTRAL UNITS ? See pages XX and XX

SCROLLING INTERCOM

CENTRAL UNITS



1 door - 03-0102



2 doors - 03-0101

CENTRAL UNIT CHARACTERISTICS	Maximum number of dwellings managed	200	1,000
	Power supply recommended (not included)	12 VDC 5A - 24 VDC 2,5A	
SYSTEM	Number of relays	1 (+3)	2 (+2)

SERVICE PACKAGE CHOICE

Once you've selected your equipment, take out the package of your choice to ensure the intercom's functionality.

**DON'T FORGET TO ADD
YOUR SERVICE PACKAGE !**

CLASSIC
SERVICE PACKAGE

PREPAID
15 YEARS
ALL INCLUSIVE PACKAGE

See pages XX and XX TO DISCOVER THE OFFERS

4G-IP MODULE CHARACTERISTICS	4G-IP module	Deported
	Number of intercom(s) per 4G-IP module (video)	1 to 3 (depending on the type of central unit)

SIMPLIFIED SCHEME* and WIRING

