

SQUARE PROXIMITY READER

- + Can be integrated in an existing intercom
- + Ideal for controlling an insulated door





INSTALLATION MANUAL



ALL INCLUDED PACKAGE - intrabox

INTRABOX DATA ECO SQUARE READER	Stainless steel finish	1 square reader (04-0106) + 1 1-door central unit (03-0102) + 1 data module with unlimited data synchronisation 10 years	06-0128
---------------------------------	------------------------	--	---------

SQUARE PROXIMITY READER RANGE

SQUARE PROXIMITY READER	Stainless steel finish	04-0106	
 Surface mounted box	Stainless steel finish	12-0132	W 125.5 x H 125.50 x D 57 mm
 Flush fit back box	Stainless steel finish	12-0135	W 90.40 x H 90 x D 37 mm

DESCRIPTION and TECHNICAL SPECIFICATIONS

PROXIMITY READER

DIMENSIONS (W x H x D)	Reader	60 x 60 x 18 mm
ENVIRONMENT	Operating temperature	20°C to +60°C
	Index Protection	IP54 / IK08
INSTALLATION	Flush-mounted	✓
	Surface-mounted	Surface-mounted box available as an add-on product

CENTRAL UNITS

CENTRAL UNIT CHARACTERISTICS	1-door - 03-0102	2-door - 03-0101	Relay card - 12-0110
Number max of key fobs	3,000	7,000	10,000
Power supply recommended (not included)	12 to 24 V DC 2A mini		
DIMENSIONS (W x H x D)	74 x 59 x 18 mm		

MODULE

MODULE CHARACTERISTICS	Dimensions (W x H x D)	162 x 96 x 53 mm
-------------------------------	------------------------	------------------

ADDITIONAL INFORMATION

Technical alert	✓
Mifare compatibility	✓
Time-stamped events	✓
Free access time slots	✓

SIMPLIFIED SCHEME and WIRING

